



Glide is one of Australia's leading manufacturers of high-quality manual and powered wheelchairs.



The Centro is one of our most sold powerchairs. Its reliable and can be customised to suit a large range of clients, from complex to low need clients. Centro has all the features clients have been requesting, in a Mid Wheel Drive for many years. Australian manufactured, the Centro is designed to give remarkable stability and drive capabilities, with trouble free service for many years

APT SUSPENSION AND KERB CLIMBING

APT (Active Pozi Trak) is a unique suspension system patented by Glide that enables the Centro to climb kerbs up to 80mm high. This system increases traction on the drive wheels, aids with kerb climbing, and acts as an anti pitch device. The suspension system also eliminates nose dive when descending road side kerbs.

THE CENTRO RANGE



CENTO LIFT-ANTERIOR-REACH

The CentroGlide LAR adds electronic vertical seat raising to allow users to adjust the height to be comfortable at a desk, high bench or low coffee table.

The power lift feature also allows a user to transfer from the chair at standing height.



CENTO VERTICAL LIFT

The VL has all the industry-leading features of the CentroGlide with the additional convenience of powered seat raising.

The lift system can raise the seat height by up to 30cm. The VL can also tilt backwards, as required.



CENTO XT

The CentroGlide XT is a special version of our leading power wheelchair, with features to give users the freedom to navigate grass playing fields, dirt tracks, or uneven outdoor surfaces with confidence.

SMOOTH RIDE

The drive wheels are set positive, meaning when the wheelchair is on a level ground, a preload of up to 20kg (depending on spring set up type) is on each drive wheel. This unique system greatly improves traction for driving and braking. It also performs extremely well in emergency down hill braking.

Model	Seat width	Seat depth	Seat rise height	Tilt	Overall length	Overall width	Seat height	Battery	Max user weight
Lift anterior reach	31-61cm	31-58cm	NA	NA	900mm	620mm	46cm	40km range	150kg
Vertical lift	34-67cm	31-64cm	300mm	0-50 degrees std	900mm	620mm	46cm	70-80 amp/hr	175kg
Centro XT	31-61cm	31-58cm	NA	NA	980cm	740cm	46cm	40km range	175kg

